

- Protection class IP54
- Stroke 10...52 mm

RVAN18-230 is a valve actuator intended for control of Regin's valves. Information on which valves are suitable can be found in the product information for each valve. Regin also offers adapters for adjusting the actuator to valves of other brands.

#### Stroke and end position calibration

Stroke and end position calibration is not necessary due to a construction utilizing end position stops.

When the valve reaches the end position, a force is generated. Once the force of the actuator reaches a predefined level, the limit switch automatically halts the drive motor.

# **RVAN18-230**

Valve actuator for 3-position control, 230 V AC. Force 1800 N.

Valve actuator for control of Regin's range of valves. Actuator can be set manually.

- Manual manoeuvring
- Easy to mount on the valve
- Position indication

#### **Position indications**

There are two position indications for the stem, one red and one blue. They can be used for end position indication, since they accompany the stem to its end position. They can also be switched to indicate whether the valve is opening or closing.

#### Manual override

The valve position can be changed manually using the knob located in the actuator lid.



## Technical data

Supply voltage  $230 \text{ V AC} \pm 15 \%$ , 50 Hz

Control signal 3-position 12 W Power consumption 10...52 mm Stroke Stroke time 3 s/mm Force 1800 N 0...50°C Ambient temperature -40...+80°C Storage temperature 10...90 % RH Ambient humidity Protection class IP54



Low Voltage Directive (LVD) standards: This product conforms to the requirements of the European Low Voltage Directive (LVD) 2006/95/EC through product standards

EN60730-1:2000 and EN60730-2-14:1997.


**EMC emissions & immunity standards:** This product conforms to the requirements of the EMC Directive 2004/108/EC through product standards EN60730-1:2000 and

EN60730-2-14:1997.


RoHS: This product conforms to the Directive 2011/65/EU of the European Parliament and


of the Council.

# Wiring



## **Dimensions**





Head Office SwedenPhone:+46 31 720 02 00Web:www.regincontrols.comMail:info@regin.se

