

- Protection class IP54
- Manual operation
- Easy to mount on the valve

RVAN10-24 is a valve actuator intended for control of Regin's valves. Using an adaptor kit, the actuator can also be adapted for use with other valves on the market.

Stroke and end position calibration

Stroke and end position calibration is not necessary due to a construction utilizing end position stops.

When the valve reaches the end position, a force is generated. Once the force of the actuator reaches a predefined level, the limit switch automatically halts the drive motor.

RVAN10-24

Valve actuator for 3-point control signal. Force 1000 N.

Valve actuator for control of Regin's valves. The actuator can be operated manually.

- Stroke 10...30 mm
- Position indication

Position indications

There are two position indications for the stem, one red and one blue. They can be used for end position indication, since they accompany the stem to its end position. They can also be switched to indicate whether the valve is opening or closing.

Manual override

The valve position can be changed manually using the knob located in the actuator lid.



Technical data

Supply voltage	24 V A0
Control signal	3-point
Power consumption	Max. 8
Stroke	1030
Stroke time	3 s/mm
Force	1000 N
Ambient temperature	050°C
Storage temperature	-4080
Ambient humidity	1090%
Protection class	IP54
(This pro
••	EN6073

24 V AC ±15%, 50/60 Hz 3-point Max. 8 W 10...30 mm 3 s/mm 1000 N 0...50°C -40...80°C 10...90% RH IP54 This product conforms with the EMC requirements of European harmonised standards EN60730-1:2000 and EN60730-2-8:2002 and carries the CE mark. It also conforms with the requirements of European LVD standards EN60730-1:2000 and EN60730-2-8:2002. **RoHS**: This product conforms to the Directive 2011/65/EU of the European Parliament and of the Council.

Wiring and Dimensions

